



## Tragstationen U65

U65-DIN 1026 / EN 10365

Version: 2018-04-17



BB(mm)	Muldung°	D(mm)	RL(mm)	h(mm)	A(mm)	E(mm)	a(mm)	b(mm)	m(kg)	Artikl
500	15	89,108	200	125	740	790	25	65	7.42	<a href="#">U6505015125</a>
500	20	89,108	200	125	740	790	25	65	7.56	<a href="#">U6505020125</a>
500	25	89,108	200	125	740	790	25	65	7.66	<a href="#">U6505025125</a>
500	30	89,108	200	125	740	790	25	65	7.80	<a href="#">U6505030125</a>
500	35	89,108	200	125	740	790	25	65	8.03	<a href="#">U6505035125</a>
500	40	89,108	200	125	740	790	25	65	8.12	<a href="#">U6505040125</a>
500	45	89,108	200	125	740	790	25	65	8.20	<a href="#">U6505045125</a>
650	15	89,108	250	125	890	940	25	65	8.54	<a href="#">U6506515125</a>
650	20	89,108	250	125	890	940	25	65	8.67	<a href="#">U6506520125</a>
650	25	89,108	250	125	890	940	25	65	8.86	<a href="#">U6506525125</a>
650	30	89,108	250	125	890	940	25	65	9.01	<a href="#">U6506530125</a>
650	35	89,108	250	125	890	940	25	65	9.31	<a href="#">U6506535125</a>
650	40	89,108	250	125	890	940	25	65	9.44	<a href="#">U6506540125</a>
650	45	89,108	250	125	890	940	25	65	9.59	<a href="#">U6506545125</a>
800	15	89,108	315	125	1090	1140	25	65	10.10	<a href="#">U6508015125</a>
800	20	89,108	315	125	1090	1140	25	65	10.30	<a href="#">U6508020125</a>
800	25	89,108	315	125	1090	1140	25	65	10.45	<a href="#">U6508025125</a>
800	30	89,108	315	125	1090	1140	25	65	10.71	<a href="#">U6508030125</a>
800	35	89,108	315	125	1090	1140	25	65	10.96	<a href="#">U6508035125</a>
800	40	89,108	315	125	1090	1140	25	65	11.10	<a href="#">U6508040125</a>
800	45	89,108	315	125	1090	1140	25	65	11.35	<a href="#">U6508045125</a>
1000	15	89,108	380	125	1290	1340	25	65	11.62	<a href="#">U6510015125</a>
1000	20	89,108	380	125	1290	1340	25	65	11.85	<a href="#">U6510020125</a>
1000	25	89,108	380	125	1290	1340	25	65	12.10	<a href="#">U6510025125</a>
1000	30	89,108	380	125	1290	1340	25	65	12.33	<a href="#">U6510030125</a>
1000	35	89,108	380	125	1290	1340	25	65	12.65	<a href="#">U6510035125</a>
1000	40	89,108	380	125	1290	1340	25	65	12.85	<a href="#">U6510040125</a>
1000	45	89,108	380	125	1290	1340	25	65	13.06	<a href="#">U6510045125</a>

