



## Idler frames U10-135

U100-DIN 1026 / EN 10365

Version: 2015-07-27



BB(mm)	Inclination°	D(mm)	RL(mm)	h(mm)	A(mm)	E(mm)	a(mm)	b(mm)	m(kg)	Artikl
650	15	89,108,133	250	135	890	940	25	65	13.30	<a href="#">U1006515135</a>
650	20	89,108,133	250	135	890	940	25	65	13.50	<a href="#">U1006520135</a>
650	25	89,108,133	250	135	890	940	25	65	13.80	<a href="#">U1006525135</a>
650	30	89,108,133	250	135	890	940	25	65	14.00	<a href="#">U1006530135</a>
650	35	89,108,133	250	135	890	940	25	65	14.20	<a href="#">U1006535135</a>
650	40	89,108,133	250	135	890	940	25	65	14.50	<a href="#">U1006540135</a>
650	45	89,108,133	250	135	890	940	25	65	14.80	<a href="#">U1006545135</a>
800	15	89,108,133	315	135	1090	1140	25	65	15.60	<a href="#">U1008015135</a>
800	20	89,108,133	315	135	1090	1140	25	65	15.80	<a href="#">U1008020135</a>
800	25	89,108,133	315	135	1090	1140	25	65	16.10	<a href="#">U1008025135</a>
800	30	89,108,133	315	135	1090	1140	25	65	16.40	<a href="#">U1008030135</a>
800	35	89,108,133	315	135	1090	1140	25	65	16.70	<a href="#">U1008035135</a>
800	40	89,108,133	315	135	1090	1140	25	65	17.00	<a href="#">U1008040135</a>
800	45	89,108,133	315	135	1090	1140	25	65	17.30	<a href="#">U1008045135</a>
1000	15	89,108,133	380	135	1290	1340	25	65	17.80	<a href="#">U1010015135</a>
1000	20	89,108,133	380	135	1290	1340	25	65	18.20	<a href="#">U1010020135</a>
1000	25	89,108,133	380	135	1290	1340	25	65	18.50	<a href="#">U1010025135</a>
1000	30	89,108,133	380	135	1290	1340	25	65	18.80	<a href="#">U1010030135</a>
1000	35	89,108,133	380	135	1290	1340	25	65	19.10	<a href="#">U1010035135</a>
1000	40	89,108,133	380	135	1290	1340	25	65	19.50	<a href="#">U1010040135</a>
1000	45	89,108,133	380	135	1290	1340	25	65	19.80	<a href="#">U1010045135</a>
1200	15	89,108,133	465	135	1530	1590	30	65	20.70	<a href="#">U1012015135</a>
1200	20	89,108,133	465	135	1530	1590	30	65	21.10	<a href="#">U1012020135</a>
1200	25	89,108,133	465	135	1530	1590	30	65	21.50	<a href="#">U1012025135</a>
1200	30	89,108,133	465	135	1530	1590	30	65	21.90	<a href="#">U1012030135</a>
1200	35	89,108,133	465	135	1530	1590	30	65	22.30	<a href="#">U1012035135</a>
1200	40	89,108,133	465	135	1530	1590	30	65	22.80	<a href="#">U1012040135</a>
1200	45	89,108,133	465	135	1530	1590	30	65	23.20	<a href="#">U1012045135</a>
1400	15	89,108,133	530	135	1730	1790	30	65	23.00	<a href="#">U1014015135</a>
1400	20	89,108,133	530	135	1730	1790	30	65	23.40	<a href="#">U1014020135</a>
1400	25	89,108,133	530	135	1730	1790	30	65	23.80	<a href="#">U1014025135</a>
1400	30	89,108,133	530	135	1730	1790	30	65	24.30	<a href="#">U1014030135</a>
1400	35	89,108,133	530	135	1730	1790	30	65	24.90	<a href="#">U1014035135</a>
1400	40	89,108,133	530	135	1730	1790	30	65	25.30	<a href="#">U1014040135</a>
1400	45	89,108,133	530	135	1730	1790	30	65	25.80	<a href="#">U1014045135</a>

