


Idler frames

Version:



BB(mm)	Inclination°	D(mm)	RL(mm)	h(mm)	A(mm)	E(mm)	a(mm)	b(mm)	m(kg)	Artikl
650	15	89,108,133	250	150	890	940	25	65	13.70	U1006515150
650	20	89,108,133	250	150	890	940	25	65	13.90	U1006520150
650	25	89,108,133	250	150	890	940	25	65	14.10	U1006525150
650	30	89,108,133	250	150	890	940	25	65	14.30	U1006530150
650	35	89,108,133	250	150	890	940	25	65	14.50	U1006535150
650	40	89,108,133	250	150	890	940	25	65	14.90	U1006540150
650	45	89,108,133	250	150	890	940	25	65	15.10	U1006545150
800	15	89,108,133	315	150	1090	1140	25	65	15.90	U1008015150
800	20	89,108,133	315	150	1090	1140	25	65	16.10	U1008020150
800	25	89,108,133	315	150	1090	1140	25	65	16.40	U1008025150
800	30	89,108,133	315	150	1090	1140	25	65	16.70	U1008030150
800	35	89,108,133	315	150	1090	1140	25	65	17.00	U1008035150
800	40	89,108,133	315	150	1090	1140	25	65	17.40	U1008040150
800	45	89,108,133	315	150	1090	1140	25	65	17.70	U1008045150
1000	15	89,108,133	380	150	1290	1340	25	65	18.20	U1010015150
1000	20	89,108,133	380	150	1290	1340	25	65	18.50	U1010020150
1000	25	89,108,133	380	150	1290	1340	25	65	18.80	U1010025150

1000	30	89,108,133	380	150	1290	1340	25	65	19.10	U1010030150
1000	35	89,108,133	380	150	1290	1340	25	65	19.50	U1010035150
1000	40	89,108,133	380	150	1290	1340	25	65	19.90	U1010040150
1000	45	89,108,133	380	150	1290	1340	25	65	20.30	U1010045150
1200	15	89,108,133	465	150	1530	1590	30	65	21.00	U1012015150
1200	20	89,108,133	465	150	1530	1590	30	65	21.40	U1012020150
1200	25	89,108,133	465	150	1530	1590	30	65	22.10	U1012025150
1200	30	89,108,133	465	150	1530	1590	30	65	22.50	U1012030150
1200	35	89,108,133	465	150	1530	1590	30	65	22.70	U1012035150
1200	40	89,108,133	465	150	1530	1590	30	65	23.10	U1012040150
1200	45	89,108,133	465	150	1530	1590	30	65	23.60	U1012045150
1400	15	89,108,133	530	150	1730	1790	30	65	23.30	U1014015150
1400	20	89,108,133	530	150	1730	1790	30	65	23.70	U1014020150
1400	25	89,108,133	530	150	1730	1790	30	65	24.20	U1014025150
1400	30	89,108,133	530	150	1730	1790	30	65	24.70	U1014030150
1400	35	89,108,133	530	150	1730	1790	30	65	25.20	U1014035150
1400	40	89,108,133	530	150	1730	1790	30	65	25.70	U1014040150
1400	45	89,108,133	530	150	1730	1790	30	65	26.10	U1014045150